

BEST AVAILABLE COPY

Serial No. 10/690,098

- 3 -

JAN 10 2006

50703sh

CLAIM AMENDMENTS

1-23. (Canceled)

24. (Currently Amended) A liquid receptacle for rapidly lowering the temperature of a liquid contained therein to a warm range suitable for human contact and maintaining the liquid in the warm range for an extended period of time, said receptacle comprising:

an inner vessel having an open upper end and closed lower end and a wall connecting the upper end and the lower end;

a one piece [[an]] insulated outer shell spaced from the inner vessel defining an interstitial chamber therebetween, the outer shell including an inner layer and an outer layer with an evacuated void therebetween for vacuum insulating the outer shell; and

a phase change material disposed within the chamber for regeneratively absorbing thermal energy from the liquid and then releasing the thermal energy to the liquid to maintain the temperature of the liquid.

25. (Previously Presented) The liquid receptacle according to claim 24, wherein the inner layer of the outer shell has an inner surface, the upper end of the inner vessel being in sealing engagement with the inner surface of the outer wall.

26. (Previously Presented) The liquid receptacle according to claim 25, wherein the outer shell has an upper edge terminating in a lip for drinking, the lip being spaced from the upper end of the inner vessel by a distance sufficient to prevent contact between the inner vessel and the mouth of a consumer of liquid from the receptacle.

27. (Previously Presented) The liquid receptacle according to claim 25, wherein the outer shell has an upper edge terminating in a lip for drinking, the lip having a cross section comprising at least 180 degrees of an arc.

Serial No. 10/690,098

- 4 -

50703sb

28. (Previously Presented) The liquid receptacle according to claim 24, wherein the outer shell has an upper edge terminating in a lip for drinking, the lip being spaced from the upper end of the inner vessel by a distance sufficient to prevent contact between the inner vessel and the mouth of a consumer of liquid from the receptacle.

29. (Previously Presented) The liquid receptacle according to claim 24, wherein the outer shell has an upper edge terminating in a lip for drinking, the lip having a cross section comprising at least 180 degrees of an arc.

30. (Previously Presented) The liquid receptacle according to claim 24, wherein the wall of the inner vessel has an outward taper such that the upper end has a width greater than a width of the lower end.

31. (Currently Amended) The liquid receptacle according to claim 24, wherein the phase change material has a solid to liquid phase change temperature within the range of 110°F degrees Fahrenheit to 160°F degrees Fahrenheit.

32. (Previously Presented) A receptacle according to claim 31, wherein the phase change material is selected from the group consisting of naturally occurring fatty acids.

33. (Previously Presented) A receptacle according to claim 24, wherein the phase change material is palmitic acid.

34. (Previously Presented) The liquid receptacle according to claim 24, wherein the inner vessel is formed from a material having a thermal conductivity greater than 150 Watts/meter-degree Kelvin.

35. (Previously Presented) The liquid receptacle according to claim 24, wherein the material is selected from the group consisting of aluminum, aluminum alloys, copper, and copper alloys.

Serial No. 10/690,098

- 5 -

50703sh

36. (Withdrawn) The liquid receptacle according to claim 24, wherein the receptacle is a baby bottle.

37. (Withdrawn) The liquid receptacle according to claim 24, wherein the receptacle is a bathing tub.

38. (Currently Amended) A liquid receptacle for rapidly lowering the temperature of a hot beverage contained therein to a warm range suitable for human consumption and maintaining the liquid in the warm range for an extended period of time, said receptacle comprising:

an inner vessel having an open upper end and closed lower end and a wall connecting the upper end and the lower end, the upper end terminating in a rim;

a one piece [(an)] insulated outer shell spaced from the inner vessel defining an interstitial chamber therebetween, the outer shell having an inner surface and an outer surface and an upper edge terminating in a lip for drinking;

the inner surface of the outer shell having a circumferential outwardly extending recess defined therein, the recess being spaced from the lip;

the rim of the inner vessel being in sealing engagement with the recess in the inner surface of the outer shell and spaced from the lip of the outer shell for preventing contact between the inner vessel and the mouth of a consumer of liquid from the receptacle; and

a phase change material disposed within the chamber for regeneratively absorbing thermal energy from the beverage and then releasing the thermal energy to the beverage to maintain the temperature of the liquid.

39. (Previously Presented) The liquid receptacle according to claim 38, wherein the outer shell has an inner layer and an outer layer with an evacuated void therebetween for vacuum insulating the outer shell.

40. (Previously Presented) The liquid receptacle according to claim 38, wherein the upper end of the inner vessel is spaced from the lip by a distance greater than .125 inches.

Serial No. 10/690,098

- 6 -

50705sh

41. (Canceled)

42. (Previously Presented) The liquid receptacle according to claim 38, wherein the wall of the inner vessel has an outward taper such that the upper end has a width greater than the width of the lower end.

43. (Canceled)

44. (New) A liquid receptacle for rapidly lowering the temperature of a hot beverage contained therein to a warm range suitable for human consumption and maintaining the liquid in the warm range for an extended period of time, said receptacle comprising:

an inner vessel having an open upper end and closed lower end and a wall connecting the upper end and the lower end, the upper end terminating in a bulbous lip;

an insulated outer shell spaced from the inner vessel defining an interstitial chamber therebetween, the outer shell having an inner surface and an outer surface and an upper edge terminating in a lip for drinking;

the inner surface of the outer shell having a circumferential outwardly extending arched recess defined therein, the recess being spaced from the lip;

the lip of the inner vessel being in sealing engagement with the recess in the inner surface of the outer shell and spaced from the lip of the outer shell for preventing contact between the inner vessel and the mouth of a consumer of liquid from the receptacle;

a phase change material disposed within the chamber for regeneratively absorbing thermal energy from the beverage and then releasing the thermal energy to the beverage to maintain the temperature of the liquid.

45. (New) The liquid receptacle according to claim 44, wherein the outer shell has an inner layer and an outer layer with an evacuated void therebetween for vacuum insulating the outer shell.

46. (New) The liquid receptacle according to claim 45, wherein the inner layer and outer layer

Serial No. 10/690,098

- 7 -

50703sh

are formed of metal.

47. (New) The liquid receptacle according to claim 44, wherein the upper end of the inner vessel is spaced from the lip by a distance greater than .125 inches.

48. (New) The liquid receptacle according to claim 44, wherein the lip of the outer shell has a cross section comprising at least 180 degrees of an arc.

49. (New) The liquid receptacle according to claim 44, wherein the phase change material has a solid to liquid phase change temperature within the range of 110°F to 160°F.

50. (New) A receptacle according to claim 44, wherein the phase change material is selected from the group consisting of naturally occurring fatty acids.

51. (New) A receptacle according to claim 44, wherein the phase change material is palmitic acid.

52. (New) The liquid receptacle according to claim 44, wherein the inner vessel is formed from a material having a thermal conductivity greater than 150 Watts/meter-degree Kelvin.

53. (New) The liquid receptacle according to claim 51, wherein the material is selected from the group consisting of aluminum, aluminum alloys, copper, and copper alloys.

54. (New) The liquid receptacle according to claim 44, wherein the insulated outer shell is at least partially formed of plastic.

55. (New) The liquid receptacle according to claim 53, wherein the insulated outer shell includes an inner layer and an outer layer formed of plastic with an air gap disposed therebetween.

Serial No. 10/690,093

- 8 -

50703sh

56. (New) The liquid receptacle according to claim 44, wherein the insulated outer shell is at least partially formed of metal.

57. (New) The liquid receptacle according to claim 55, the insulated outer shell includes an inner layer and an outer layer formed of metal with an air gap disposed therebetween.

58. (New) A liquid receptacle for rapidly lowering the temperature of a liquid contained therein to a warm range suitable for human contact and maintaining the liquid in the warm range for an extended period of time, said receptacle comprising:

an inner vessel having an open upper end and closed lower end and a wall connecting the upper end and the lower end;

an insulated outer shell spaced from the inner vessel defining an interstitial chamber therebetween, the outer shell including an inner layer and an outer layer with an evacuated void therebetween for vacuum insulating the outer shell, the outer layer of the outer shell forming at least part of the outer surface of the liquid receptacle; and

a phase change material disposed within the chamber for regeneratively absorbing thermal energy from the liquid and then releasing the thermal energy to the liquid to maintain the temperature of the liquid.

TROY, MICHIGAN 48007-7121 (248) 647-6000
2701 TROY CENTER DR., SUITE 330, P.O. BOX 7021
GIFFORD, KRASS, GROH, SPRINKLE, ANDERSON & CITKOWSKI, P.C.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.